



PATENT ABSTRACTS OF JAPAN

(11) Publication number: **2000070722 A**(43) Date of publication of application: **07.03.00**

(51) Int. Cl.

B01J 29/44**B01D 53/94****F01N 3/10****F01N 3/28**(21) Application number: **10248117**(22) Date of filing: **02.09.98**(71) Applicant: **NISSAN MOTOR CO LTD**(72) Inventor: **AKAMA HIROSHI
KAMIKUBO MASANORI
ITO JUNJI**(54) **EXHAUST GAS PURIFICATION CATALYST**

(57) Abstract:

PROBLEM TO BE SOLVED: To obtain an exhaust gas purification catalyst capable of efficiently removing NOx even under the exhaust condition of a low HC to NOx ratio.

SOLUTION: A honeycomb monolithic carrier is coated with a catalyst layer contg. a catalyst material contg. a refractory inorg. compd. with pores of ≤ 1 nm diameter and a catalyst material

contg. a refractory inorg. compd. with pores of ≈ 2 nm diameter to obtain the objective exhaust gas purification catalyst. The temp. difference between the NOx reduction activity temp. ranges of the former and latter catalyst materials is less than 30°C. In other way, an inner layer contg. the former catalyst material is formed on the carrier and a surface layer contg. the latter catalyst material is laminated on the inner layer.

COPYRIGHT: (C)2000,JPO